

Others

Model 品名	Frequency 周波数 (MHz)	Mode 通倍数	Pole 次数	Pass Bandwidth 通過帯域幅		Stop Bandwidth 減衰帯域幅		Ripple リップル	Loss 挿入損失	Ultimate Attenuation 保証減衰量	Terminating Impedance 終端インピーダンス		Case Code ケースコード	
				(dB)	(kHz)	(dB)	(kHz)	(dB)	(dB)	(dB)	(f0±kHz)	Zt(//pF)		Zc(pF)
45SS7.5B	45.000	FUND	4	3	±3.75	30	±12.5	1.0	4.0	80	-910	350//6.5	18.0	7050M4
45SS15B	45.000	FUND	4	3	±7.5	35	±25	1.0	3.0	80	-910	650//3.0	9.0	7050M4
45SS20B	45.000	FUND	4	3	±10.0	25	±25	1.0	3.0	80	-910	500//2.5	9.0	7050M4
45SS30B	45.000	FUND	4	3	±15.0	30	±50	1.0	3.0	80	-910	1200//0.7	3.5	7050M4
73.35SS13B	73.350	3rd	4	3	±6.5	30	±20	1.0	4.0	70	-910	1700//−0.6	−1.3	7050M4

Dimensions(Unit:mm)

Code 7050M4

