



TEMPERATURE COMPENSATED VOLTAGE CONTROLLED CRYSTAL OSCILLATORS TCVCXO 5 × 3.2mm SMD Type

CO-TS5032 Clipped Sine Wave series

Type	型式	CO-TS5032	CO-TS5032V
Frequency Range	周波数範囲	10MHz ~ 26MHz	
Frequency Stability	周波数温度特性	±1.5ppm, ±2.0ppm, ±2.5ppm(-30 to +75°C) ±2.5ppm, ±3.0ppm(-40 to +85°C)	
Supply Voltage	供給電圧	2.7 to 5.0V	
Input Current	消費電流	2.0mA max	
Output Level	出力電圧	0.8Vp-p (Clipped sine wave)	
Output Load	出力負荷	10KΩ ±10%/10pF ±10%	
Load Change	負荷変動	±0.2ppm (10KΩ ±10%/10pF ±10%)	
Control Voltage Range	制御電圧	—	1.5V ±1.0V
Frequency Deviation	周波数制御特性	±8ppm, ±10ppm, ±15ppm	
Frequency / Supply Voltage	周波数偏差/電圧	±0.2ppm/Vcc ±5.0%	
Frequency Adjustment	周波数調整	Trimmer Less	
Aging	エージング	±1.0ppm / Year	
Phase Noise	位相ノイズ	-135dBc/Hz typ. (1.0KHz)	
Storage Temp. Range	保存温度範囲	-40 to +85°C	

Dimensions(Unit:mm)

CO-TS5032 and CO-TS5032V

